



# EZYFLEX® BI

## Butyl hose with stainless steel braid DN15 to 26

### Heating

Heating appliances



#### ► Composition:

- Butyl tube
- AISI 304 stainless steel braid with double blue edging
- Brass fittings (except nickel-plated brass elbow DN20 and 26)
- Stainless steel crimping bushings

#### ► Sealing:

- Flat gasket on flat seat (optional)

#### ► Standard lengths:

300, 500, 700, 1000 mm

#### ► Application:

Hot and cold water supply for heating appliances

#### ► Technical data



Maximum temperature  
**+90°C (peaks to +110°C)**



DN	Nom. pressure (in bar)	Max. Pressure (in bar)
15, 20, 26	10	16



**15 x 22 mm (DN15)**  
**20 x 28 mm (DN20)**  
**26 x 35 mm (DN26)**






Oxygen barrier according to DIN 4726 preventing the formation of sludge, micro-organisms and algae

#### CUSTOM OFFER

- Specific length: **150 mm to over 10,000 mm**  
MOQ depending on the desired length
- Customisable fittings: diameter, material, etc.
- Customisable packaging: contact us

#### ► Assembled hoses / References & Configurations

Reference	DN (mm)	Hose	Fitting 1 Thread	Fitting 2 Thread	Bending radius (mm)
BI15P2M2	15		Female	1/2"	88
BI15P4M4				3/4"	
BI20P4M4	20			3/4"	112
BI26P5M5	26			1"	140
BI15P2P2	15		Female	1/2"	88
BI15P4P4				3/4"	
BI20P4P4	20			3/4"	112
BI26P5P5	26			1"	140
BI15P2C2	15		Female	1/2"	88
BI15P4C4				3/4"	
BI20P4C4	20*			3/4"	112
BI26P5C5	26*			1"	140

\*Female nickel-plated brass elbow fitting



IFT Groupe Omerin SAS  
Zone Industrielle - F 63600 Ambert  
Tel: +33 (0)4 73 82 32 33  
ift@omerin.com

[www.flexibles.com](http://www.flexibles.com)

The information provided on this data sheet is indicative and subject to change without notice. All hoses ordered must comply with IFT's installation recommendations, which can be viewed in its catalogue. IFT can under no circumstances be held liable for any incidents arising from inappropriate use, particularly in the case of installation not carried out in accordance with the rules of the trade and the standards in force. © Registered trademark of IFT. Drawings and photos are not contractually binding. Reproduction is prohibited without the prior consent of IFT.