


QUAL'IFT® EI
EPDM hose with stainless steel braid DN08 to 50

► Composition:

- EPDM tube according to EN 681-1 type WB
- AISI 304 stainless steel braid

► Lengths:

See table below

Roll packaging

(other types of packaging on request)

► Application:

- Water flow for sanitary, heating and air-conditioning applications (max glycol content : 40%)
- Aqueous solutions

► Technical data

 Operating temperature
-15°C to +90°C peaks at +110°C


DN	Nom. pressure (in bar)	Max. Pressure (in bar)
08, 10, 12	16	20
15, 20, 26	10	16
33	6	6



See table below


KEY BENEFITS

- Excellent corrosion and ageing resistance
- Absorbs expansion and water hammer
- Accidental abrasion resistance
- Good UV resistance
- Does not transmit hose noise


ASSEMBLY

- **QUAL'IFT®** hoses must be assembled by scrupulously following the recommended rules and stages in paragraph "Recommendations for use"


CUSTOM OFFER

- Contact us for all your specific requirements

► Hoses for your low-pressure applications / References

Reference	DN (mm)	Diameter int. x ext. (mm)	Burst pressure (Bar)	MOQ (m)	Bending radius (mm)
EI 08	08	8.5 x 12	110	25	48
EI 10	10	9.5 x 14			60
EI 12	12	12 x 18	90	25	72
EI 15	15	15 x 22	80	25	88
EI 20	20	20 x 28	60	20	112
EI 26	26	26 x 35	45	30	140
EI 33	33	33 x 43	40	20	172
EI 40	40	40 x 50	30	Contact us	392
EI 50	50	50 x 63			488