



UMSF fitting

Female male union with spherical-tapered seat



► **Composition:**

- Brass
- Gas thread according to ISO 228
- Other materials on request (nickel-plated brass, stainless steel, etc.)

► **Packaging:**

- In bags
- Other packaging types on request

► **Assembly:**

UMSF fittings can be used with spherical-tapered fittings: PSM, RCPS

► **Sealing:**

Metal / Metal (A thread)
Flat gasket on flat seat (B thread)

► **Application:**

All low-pressure applications

ASSEMBLY

► IFT fittings must be assembled by scrupulously following the recommended rules and stages in paragraph "Recommendations for use"

CUSTOM OFFER

► Contact us for all your specific requirements

► **Fittings for your low-pressure applications / References & Compositions**

Reference	Material	Male thread spherical-tapered		Female thread	
		mm	inches	mm	inches
UMSF01LAG	Brass	8 x 13	1/4"	12 x 17	3/8"
UMSF0LAG				8 x 13	1/4"
UMSF10LAG		12 x 17	3/8"	8 x 13	1/4"
UMSF12LAG				15 x 21	1/2"
UMSF1LAG				12 x 17	3/8"
UMSF21LAG		15 x 21	1/2"	12 x 17	3/8"
UMSF24LAG				20 x 27	3/4"
UMSF2LAG				15 x 21	1/2"
UMSF42LAG				15 x 21	1/2"
UMSF4LAG		20 x 27	3/4"	20 x 27	3/4"
UMSF5LAG				26 x 34	1"
UMSF6LAG		33 x 42	1"1/4	33 x 42	1"1/4
UMSF7LAG				40 x 49	1"1/2